

POCKET DOSIMETER



Technical Specification

Radiation Detected	: Gamma
Display	: 6-digit LCD with momentary illumination for dark/ low light conditions
Measurement	: 1µSv to 999999µSv
Range Immunity to EMI	: Unaffected by mobile phones in close proximity, Does not stop monitoring dose even under effect of strong mobile data / call signals (Especially in poor network area) or any other signals.
Energy response	: ± 25%
Accuracy	: ± 15% (Cs-137)
Switch	: ON/ OFF
Accumulated Dose Retention & Reset	: Power Off or low battery or battery removal doesn't affect the accumulated dose reading. However reset facility is given to reset accumulated dose.
Battery	: CR 2354 Lithium coin cell (3V)
Battery life	: Min 1000hrs.
Dimensions	: 30mm x 100mm x 15mm approx.
Enclosure	: PEN-type enclosure
Weight	: 65 grams
Shock Protection	: Rubber sleeve

CAT.NO. : PDM 2/0320

PLA ELECTRO APPLIANCES PVT. LTD.

THAKOR INDUSTRIAL ESTATE, KURLA - KIROL ROAD, VIDYAVIHAR (WEST), MUMBAI - 400 086
TEL : 2511 6864 / 6865 FAX : 91-22 - 2516 8948 WEB : www.plaelectro.com E-Mail : pla@plaelectro.com