

MICRO-R RADIATION SURVEY METER

SALIENT FEATURES

- **HAND HELD • PORTABLE • LIGHTWEIGHT • ANALOG DOSE RATE METER • PLASTIC SCINTILLATOR**



TECHNICAL SPECIFICATION

Radiation Detector	: Gamma
Display	: Analogue Panel Meter (Scale Illuminated)
Range	: Five linear ranges from 0 to 200mR/h (0 – 20 μ R/h, 0 - 200 μ R/h, 0 – 2 mR/h, 0 – 20mR/h, 0 – 200mR/h)
Detector	: Internal, scintillator (plastic) with 1” dia PMT.
Accuracy	: within 10% of reading for Cs-137
Facility Check	: HV Check / Battery Check
Batteries	: 1.5V x 6 Nos. (AA size Dry Cell)
Weight	: 1.5Kg approx.
Dimension	: 23cm x 9cm x 10cm approx., handle dimensions extra

CAT.NO. PRM121P/0210

PLA ELECTRO APPLIANCES PVT. LTD.

THAKOR INDUSTRIAL ESTATE, KURLA - KIROL ROAD, VIDYAVIHAR (WEST), MUMBAI - 400 086
TEL : 2511 6864 / 6865 FAX : 91-22 - 2516 8948 WEB : www.plaelectro.com E-Mail pla@bom3.vsnl.net.in